



Cassette Inverter

- Meeting requirement from 12 000 btu/h to 60 000 btu/h with excellent and energy saving performance.
- Universal outdoor units with and diversified indoor units satisfy customized decoration.
- Free combination and easy installation.
- Long distance monitoring, weekly timer and low ambient cooling are optional.



Southern Africa: Sales/Distribution solely by JA-SA import & export
www.jet-air.co.za



Jet-Air®

Cassette Inverter



Model No.	Outdoor	JASA-H12A4/FIU	JASA-H18A4/FIU	JASA-H24A4/FIU	JASA-H30A4/FIU	JASA-H36A4/FIU
Model No.	Indoor	JASA-Ca-H12A4/FI	JASA-Ca-H18A4/FI	JASA-Ca-H24A4/FI	JASA-Ca-H30A4/FI	JASA-Ca-H36A4/FI
Power supply	Outdoor	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50
Power supply	Indoor	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50
Cooling capacity	BTU/H	11942	17060	23884	28320	34120
Cooling input	kW	1.09	1.6	2.18	2.67	3.2
Cooling current	A	5.4	7.5	10.1	12.4	15
Heating capacity	BTU/H	12966	19107	27296	31390	40944
Heating input	kW	1.05	1.58	2.21	2.57	3.4
Heating current	A	4.9	7.4	10.2	12	15.5
Indoor dimensions	mm (W×D×H)	596×596×240	596×596×240	840×840×240	840×840×320	840×840×320
Panel	mm (W×D×H)	650×650×50	650×650×50	950×950×60	950×950×60	950×950×60
Outdoor dimensions	mm (W×D×H)	848×320×540	955×396×700	980×427×790	980×427×790	1107×440×1100
Indoor packing	mm (W×D×H)	773×773×300	773×773×300	963×963×325	963×963×325	963×963×325
Panel packing	mm (W×D×H)	763×763×105	763×763×105	1028×1028×130	1028×1028×130	1028×1028×130
Outdoor packing	mm (W×D×H)	881×363×595	1029×458×750	1083×448×855	1083×448×855	1158×493×1235
Indoor Weight	N. W./G.W. Kg	20/24	20/24	26/32	31/38	31/38
Outdoor Weight	N. W./G.W. Kg	34/37	47/50	67/72	71/76	92/100
Liquid pipe	inch (mm)	Φ1/4 (6.35)	Φ1/4 (6.35)	Φ3/8 (9.52)	Φ3/8 (9.52)	Φ3/8 (9.52)
Gas pipe	inch (mm)	Φ3/8 (9.52)	Φ1/2 (12.7)	Φ5/8 (15.9)	Φ5/8 (15.9)	Φ5/8 (15.9)

Model No.	Outdoor	JASA-H36A5/FIU	JASA-H42A4/FIU	JASA-H42A5/FIU	JASA-H48A4/FIU	JASA-H48A5/FIU	JASA-H60A5/FIU
Model No.	Indoor	JASA-Ca-H36A4/FI	JASA-Ca-H42A4/FI	JASA-Ca-H42A4/FI	JASA-Ca-H48A4/FI	JASA-Ca-H48A4/FI	JASA-Ca-H60A4/FI
Power supply	Outdoor	380-415V-3-50	220-240V-1-50	380-415V-3-50	220-240V-1-50	380-415V-3-50	380-415V-3-50
Power supply	Indoor	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50	220-240V-1-50
Cooling capacity	BTU/H	34120	39238	39238	47768	47768	54592
Cooling input	kW	3.12	3.9	3.9	4.8	4.8	5.75
Cooling current	A	5.6	18.1	6.7	22.3	8.2	10
Heating capacity	BTU/H	40944	46062	46062	54592	54592	58004
Heating input	kW	3.7	3.74	4.3	4.4	4.4	4.7
Heating current	A	6	17.2	6.5	20	7.6	8.2
Indoor dimensions	mm (W×D×H)	840×840×320	840×840×320	840×840×320	910×910×290	910×910×290	910×910×290
Panel	mm (W×D×H)	950×950×60	950×950×60	950×950×60	1040×1040×65	1040×1040×65	1040×1040×65
Outdoor dimensions	mm (W×D×H)	1107×440×1100	958×412×1349	958×412×1349	958×412×1349	958×412×1349	1085×427×1365
Indoor packing	mm (W×D×H)	963×963×325	963×963×325	963×963×325	1023×993×375	1023×993×375	1023×993×375
Panel packing	mm (W×D×H)	1028×1028×130	1028×1028×130	1028×1028×130	1137×1137×140	1137×1137×140	1137×1137×140
Outdoor packing	mm (W×D×H)	1158×493×1235	1043×453×1500	1043×453×1500	1043×453×1500	1043×453×1500	1143×478×1505
Indoor Weight	N. W./G.W. Kg	31/38	31/38	31/38	43/50	43/50	43/50
Outdoor Weight	G.W./N. W. Kg	98/106	95/105	108/118	108/118	114/124	126/138
Liquid pipe	inch (mm)	Φ3/8 (9.52)	Φ3/8 (9.52)	Φ3/8 (9.52)	Φ3/8 (9.52)	Φ3/8 (9.52)	Φ3/8 (9.52)
Gas pipe	inch (mm)	Φ5/8 (15.9)	Φ5/8 (15.9)	Φ5/8 (15.9)	Φ5/8 (15.9)	Φ5/8 (15.9)	Φ3/4 (19.05)

Southern Africa: Sales/Distribution solely by JA-SA import & export
www.jet-air.co.za