



Ceiling & Floor

1. Dual-direction swing, wide swing angle

- Vertical and horizontal swing function make it possible to blow air to every corner of the room.

2. Ultra slim design

3. Flexible installation

- Install it vertically against the wall or horizontally under the ceiling, make your choice.

Cold air
Warm air
use jet-air



Model			JASA-Ce-H18A4/R1-C5	JASA-Ce-H24B4/R1-C5	JASA-Ce-H36A5/R1-C5
Capacity	Cooling	Btu/h	18000	24000	36000
		KW	5.3	7.2	10.6
	Heating	Btu/h	20000	27500	40000
		KW	5.8	8.08	11.7
Electric Date	Power Supply	V~, Hz, Ph	220~240,50,1	220~240,50,1	380~415,50,3
	Cooling Power Input	KW	1.72	2.18	3.77
	Heating Power Input	KW	1.77	2.50	3.50
	Cooling Current	A	7.90	10.09	6.76
	Heating Current	A	8.13	11.59	6.28
	EER		3.08	3.31	2.81
Performance	COP		3.28	3.24	3.34
	Air Flow Volume (Hi/Mi/L)	m ³ /h	850/680/595	1200/960/840	1500/1200/1050
	Noise Level(Hi/Mi/L)	dB(A)	43/40/34	46/43/38	50/47/41
Dimension (WXHXD)	Net	mm	929*660*205	1280*660*205	1280*660*205
	Packing	mm	1010*720*290	1360*720*290	1360*720*290
Weight	Net	kg	25	32	33
	Gross	kg	28	37	40
Piping	Liquid Side	mm	6.35(1/4)	9.52(3/8)	9.52(3/8)
	Gas Side	mm	12.7(1/2)	15.88(5/8)	15.88(5/8)
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Application Area		m ²	21-35	28-47	42-70
Stuffing Quantity	20/40/40H	set	54/115/142	50/100/124	36/71/88

Model			JASA-Ce-H48A5/R1-C5	JASA-Ce-H60A5/R1-C5
Capacity	Cooling	Btu/h	48000	60000
		KW	14.0	17.6
	Heating	Btu/h	53000	63500
		KW	15.5	18.5
Electric Date	Power Supply	V~, Hz, Ph	380~415,50,3	380~415,50,3
	Cooling Power Input	KW	4.87	5.71
	Heating Power Input	KW	5.13	5.97
	Cooling Current	A	8.88	10.42
	Heating Current	A	9.33	10.83
	EER		2.87	3.08
Performance	COP		3.02	3.10
	Air Flow Volume (Hi/Mi/L)	m ³ /h	1800/1440/1260	1800/1440/1260
	Noise Level(Hi/Mi/L)	dB(A)	51/48/42	51/48/42
Dimension (WXHXD)	Net	mm	1631*660*205	1631*660*205
	Packing	mm	1710*720*290	1710*720*290
Weight	Net	kg	44	44
	Gross	kg	52	52
Piping	Liquid Side	mm	9.52(3/8)	9.52(3/8)
	Gas Side	mm	19.05(3/4)	19.05(3/4)
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)
Application Area		m ²	56-93	64-107
Stuffing Quantity	20/40/40H	set	25/54/54	25/54/54



SOUTHERN AFRICA: SALES/DISTRIBUTION SOLELY BY
JA-SA IMPORT & EXPORT
www.jet-air.co.za